

Construction Challenges in Bowstring Steel Bridges



ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024



V.SADASIVAM, CEng MICE General Manager & Head EDRC Urban Transit SBG Heavy Civil Infrastructure IC Larsen and Toubro Ltd

Sadasivam has received his bachelor's degree in Civil engineering from Bharathiyar University (1991) and post graduate degree in Structural Engineering from College of Engineering Guindy, Anna University (1993). Overall he has 30 years of experience in various Infrastructure projects. He is mainly involved in Design and Construction engineering for High Speed Rail, Metros, Bridges and Road projects. He is one of the Panel member of Plain, Reinforced and Prestressed concrete(CED#46), Bureau of Indian Standards. He is a qualified Chartered Professional - **CEng-MICE (UK)** and LRQA certified Lead Auditor.





Bowstring Steel girder bridges are typically proposed at

- Bridges across Railway/Road Crossings where the span is significantly higher (say > 50m)
- Location warrants for Aesthetic appeal and hence enhances the beauty of neighboring area
- Transportation and Assembly of Steel Bowstring Girder modules is feasible at project location
- Limitations on availability of vertical clearance





Components of a Bowstring Steel Girder Bridge

Architectural ties (Non-Structural)







Construction of Steel Bowstring Girder Bridges can be done using one of the following methods:

- 1. Push Launching of Bowstring Girder over Track Beams (Temporary Structure)
 - This method is adopted where adequate space is not available for crane movement within the span.
 Example : Railway crossing
- 2. Crane Erection Method
 - This method is adopted where adequate space is available for crane movement
- 3. Push Launching of Bowstring Girder over Track Beams
 - Case Study 1 Construction of Tallah ROB (Railway Over Bridge)
 - Case Study 2 KMDA ROBs and Flyover





Case Study 1 - Construction of Tallah ROB (Railway Over Bridge)



Construction of Tallah ROB - Project Details



- Total Length of ROB
- Span arrangement
- Overall Deck Width
- Clear carriageway width
- Min vertical clearance
- Weight of Bowstring Girder

- : 213.470m (Total length of project within Railway Boundary)
- : 30.98m+52.08m (Bowstring)+52.08m (Bowstring)+26.25m+52.08m (Bowstring)
- : 2x12.20m
- : 2x9.5m
- : 6.25m (rail level to soffit)
- : 325 MT



Construction of Tallah ROB (Railway Over Bridge)



ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024



Bowstring Girder Span – Push Launching Method



Push Launching Method - Enabling Structures





Push Launching Method - Assembly of Bowstring Girder over approach span ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 **ING - IABSE**





Push Launching Method - Installation of Spreader Beam and Pulling frame ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 **ING - IABSE**





Push Launching Method - Launching of Assembled MO Governme ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 **ING - IABSE**





Push Launching Method - Assembly of next module in Approach Span ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 **ING - IABSE**





Push Launching Method - Launching of 1st Bowstring Girder into Railway Span ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 **ING - IABSE**







Push Launching Method - Side Shifting of 1st Bowstring Girder over Piercap ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024







Push Launching Method - Side Shifting of 1st Bowstring Girder over Piercap ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024





Side Shifting Beam

Push Launching Method - Assembly of 2nd Bowstring Girder in Approach Span ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 **ING - IABSE**





Push Launching Method - Launching of 2nd Bowstring Girder into Railway Span ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 Shyambazar

Bowstring Girder - 2

Push Launching Method - Installation of Side Shifting Beam











Push Launching Method - Installation of Stools and

Hydraulic Jacks



ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024



ING - IABSE

Push Launching Method - Lowering of Bowstring Girder-2 over Bearings



Girder-2 over Bearings ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024







Push Launching Method - Removal of Track Beam and Installation of Stools





Push Launching Method - Lowering of Bowstring Girder-1 over Bearings





Push Launching Method - Reactions at Node points of Bowstring Girder ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 **ING - IABSE**







Hilman roller with Stool connected to Bowstring Girder bottom

Push Launching Method - Reactions over Deck Slab of Approach Span



ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024

Track Beam at CP2-P10 Span (Assembly location):













Track Beam between Railway span:



Push Launching Method - 1st Bowstring Girder ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 **ING - IABSE**





Sensitivity: LNT Construction General Business

Push Launching Method - Side shifting of 1st Bowstring Girder over Piercap ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 **ING - IABSE**





Sensitivity: LNT Construction General Business

Push Launching Method - 2nd Bowstring Girder Ing-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024 ING - IABSE





Sensitivity: LNT Constructio

Completed view - Three Bowstring Girder spans erected



ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024



Sensitivity: LNT Construction





Case Study 2 - Construction of KMDA ROBs and Flyover





Project

- Client
- Contractor
- Consultant

- KMDA ROBs and Flyover
- M/s Kolkata Metropolitan Development Authority (KMDA)
- M/s L&T Construction
 - M/s L&T Ramboll Consulting Engineers Limited

Park Circus ROB

- ROB Span 70 m
- Carriageway width
- Approach Spans
- 2 X 7.5 m
 - (1 x 32.374m + 9 x 27.5m) on Park circus 7-point side
 - (8 x 27.5m + 1 x 30.126m) on EM Bypass side







Bowstring Girder Assembly and Launching







- ✓ Completion of Assembly of Bowstring Girder
- ✓ Completion of Erection of all Enabling works (Trestles and track beams etc.,)

Bowstring Girder Assembly and Launching



ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024



ELEVATION

✓ **Launching of Bowstring Girder-1** using pulling arrangements

Bowstring Girder Assembly and Launching



ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024



ELEVATION

✓ **Launching of Bowstring Girder-1** using pulling arrangements







ELEVATION

✓ **Launching of Bowstring Girder-1** using pulling arrangements







✓ The Bowstring girder-1 shall be side shifted using push-pull jack







✓ Bowstring Girder-2 is launched.







ISOMETRIC VIEW OF STOOL ARRANGEMENT ABOVE PIERCAP































Martin and

Park circus ROB Bowstring Girder - Assembly and Launching



ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024







Push pull jack ready for pulling operation













Sensitivity: LNT Construction General Business





Sensitivity: LNT Construction General Business

















Sensitivity: LNT Construction General Busine





Sensitivity: LNT Construction





Sensitivity: LNT Construction Gen





Sensitivity: LNT Construction Genera

Park circus ROB - Bowstring Girder completed view



ING-IABSE Workshop on "Design, Construction and Maintenance of Steel Bridges", Dehradun, 19th & 20th October, 2024



ING - IABSE





Bowstring Girder Bridge - Construction Challenges





- 1. Detailed Design and Fabrication Drawings Bowstring Steel girder
- 2. Selection of Construction Methodology
- 3. Construction stage analysis of permanent works to suit the Construction Methodology
- 4. Design and detailing of enabling works
- 5. Selection of construction equipment and machinery to suit Construction Methodology
- 6. Construction tolerances to enable construction friendly launching or erection
- 7. Check list Wind speed during launching, deflection, pulling force required, guiding rollers etc,.
- 8. Safety aspects Power block, protection of IR works, existing bridges etc,.
- 9. Quality aspects Fabrication works, bolts, welds, tightening works etc.,





- Fabrication of welded / bolted Bowstring Girder as per approved drawings.
- Sourcing of raw materials for fabrication shall be only from approved source.
- Physical, Mechanical and chemical testing of Raw materials shall be done from the Government approved NABL accredited laboratory.
- All the test reports shall be inspected and vetted by Railways. Selection of welding electrode, flux and wire shall be as per RDSO IRS M28, IRS M39 and IRS M46.
- All the bolts, nuts and studs shall be in accordance with Indian standards IS 1148, IS 1079, IS 1929, IS 10102.
- The paint shall be procured from RDSO approved manufacturer and as per IRS B1 2001.
- NDT of single and Double vee butt weld shall be done using USFD and radiography.
- NDT of 'T' fillet weld and lap weld shall be done using DPT in accordance with IS 3658 and RDSO approved DP kit sensite cheral Business





- Ensuring proper ingress and egress to workmen when working at height.
- Ensuring all the metal components in the vicinity of traction lines are properly earthed.
- Ensuring workmen are using PPE's that are stipulated to work near electrified lines.
- The erection activity is at Railway Station, public movement shall be restricted only to predefined safe zones.
- All movable components such crane booms, man lifts etc. shall operate at safe working zones from traction lines.
- Ensuring traffic wardens are available throughout the erection activity.
- Ensuring proper safety nets are provided below the Track Beams/Bowstring Girder to avoid fall of materials into the Railway boundary.





Thank You







